

LA-UR- 04-0409

Approved for public release;  
distribution is unlimited.

*Title:* Performance Evaluation of Bimodal Thermite Composites:  
Nano- vs Miron-Scale Particles

*Author(s):* Kevin M. Moore, Michelle L. Pantoya, and Steven F. Son

*Submitted to:* International Pyrotechnics Society Meeting, July 11-16, 2004,  
Fort Collins, CO



Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the University of California for the U.S. Department of Energy under contract W-7405-ENG-36. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Form 836 (8/00)



## Performance Evaluation of Bimodal Thermite Composites: Nano- vs Miron Scale Particles

Kevin Moore<sup>1</sup>, Michelle Pantoya<sup>1</sup>, Steve Son<sup>2</sup>

<sup>1</sup> Mechanical Engineering Department, Texas Tech University, Lubbock, TX 79409

<sup>2</sup> Los Alamos National Laboratory, Los Alamos, NM, 87545

In recent years many studies of metastable interstitial composites (MIC) have shown vast combustion improvements over traditional thermite materials. The main difference between these two materials is the size of the fuel particles in the mixture. Decreasing the fuel size from the micron to nanometer range significantly increases the combustion wave speed and ignition sensitivity. Little is known, however, about the critical level of nano-sized fuel particles needed to enhance the performance of the traditional thermite. Ignition sensitivity experiments were performed using Al/MoO<sub>3</sub> pellets at a theoretical maximum density of 50% (2 g/cm<sup>3</sup>). The Al fuel particles were prepared as bi-modal size distributions with micron (i.e., 4 and 20  $\mu$ m diameter) and nano-scale Al particles. The micron-scale Al was replaced in 10% increments by 80 nm Al particles until the fuel was 100% 80 nm Al. These bi-modal distributions allow the unique characteristics of nano-scale materials to be better understood. The pellets were ignited using a 50-W CO<sub>2</sub> laser. High speed imaging diagnostics were used to measure ignition delay times, and micro-thermocouples were used to measure ignition temperatures. Combustion wave speeds were also examined.